

Model 5532 OFF/SVCN/XNET/GPCN Display Indicator Unit

- Conference Room Application: Model 5532 Displays the OFF/SVCN/XNET/GPCN Status of the Model 5535 Switch.

INTRODUCTION

The Model 5532 is designed to display the isolation/connection status of the Model 5535 Single Channel 4-State Cat5e switch. Users can link these units to create a robust conference communications switching system. The dimensions of the Model 5532 are 1.75"H x 6.75"D x 19"W and the unit mounts in a standard 1U equipment rack. The unit weight is approximately 2.0 lbs.

FEATURES

- The front panel LED Display on the Model 5532 will display the OFF/SVCN/XNET/GPCN status of the connected Model 5535 switch.
- Display Indicator unit connects to status port of the Model 5535 switch.
- Display is always showing one of the four possible states of the companion switch.
- Power for the LED's of the Model 5535 switch is provided via the Control port of the Model 5532 Display Indicator Unit.**
- Installs in a standard 19" wide equipment rack. Occupies only 1U height (1.75").
- Power: UL approved 100VAC/240VAC, 50 Hz/60Hz wall mount power module supplies 12VDC, 500mA to the unit.

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) **CE and UL** listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. **Ideal for international applications.**

