

SPECIFICATIONS MODEL 5536

Cat. No. 305536

Model 5536 4-State OFFLINE/TS/SVCN/DRAG RJ45 Cat5e Keylock Switch

Ideal for secure conference room communication applications.

INTRODUCTION

The Model 5536 4-State OFFLINE/TS/SVCN/DRAG RJ45 Cat5e Switch allows the user the capability of accessing three separate devices connected to ports TS, SVCN, and DRAG via a connection through a device connected to the COMMON port, or isolating all ports in the OFFLINE position. The Model 5536 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES

- Unit switched via front panel Keylock Actuator.
- The position will follow the Keylock Actuator position at all times.
- The front panel indicator LED's will display the position status of the unit when power is connected.
- All (8) pins of the RJ45 interface are switched.
- High quality sealed switch with self-wiping low impedance contacts.
- Certified for Cat5e compliance.
- The switch ports are transparent to all data.
- The key can only be removed from the Keylock Actuator in the OFFLINE position.
- No power is required to operate unit.
- Contact Closure Status port provides dry contact logic to obtain the switch position.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length Cat5e cables available for your switch installation.
- Lifetime guarantee against manufacturing defects.



SPECIFICATIONS:

PORT CONNECTORS: (4) RJ45 female connectors labeled TS, SVCN, DRAG and COMMON.

FRONT PANEL CONTROLS: (1) Four-position keylock actuator to select OFFLINE, TS, SVCN and DRAG position.

DISPLAY: (3) Front panel Red LED's and (1) Green LED displays switch position and power status.

STATUS PORT: (1) DB9 (F) Custom Contact Closure Monitor port.

POWER: "WIDE RANGE" CE and UL listed table power module (Cat. No. 521895) 100VAC/240VAC, 50Hz/60Hz is included with the unit. This power supply is required only to power the LED's. No power is required to operate the switch.

DIMENSIONS: 19" W x 1.75" H x 8.0" D.

(48.3 x 4.5 x 20.4 cm) **WEIGHT:** 4.2 lbs.(1.9 kg)

