

QuickSwitch® 6288: ST Fiber Optic Mirror A/B Switch with Remote

INTRODUCTION

The **QuickSwitch® 6288** ST Fiber Optic Mirror A/B Switch with Remote Serial Control allows the user the capability of accessing two separate devices, ports A & B, via connection through a device connected to the Common port of the switch. The system affords local and remote access functionality.

OPERATION

The switch position may be controlled manually via a front panel pushbutton, or remotely from an RS232 serial port located on the rear of the unit. To switch manually, simply depress the front panel pushbutton and the switch will change to the new selected position as indicated by the front panel LED's. Remote switching of the unit is done through an RS232 (DB9) serial port located on the rear of the **QuickSwitch® 6288** which may be connected to any standard RS232 port on a computer. The computer, once connected to the remote port, may use any common terminal emulation software.

FEATURES:

- Control via front panel pushbutton or over Remote port on rear panel.
- Remote port is RS232, DB9/female port.
- LED's display switch position and power status.
- If power is lost, switch will default to A position (prime) and continue to pass data.
- A and B ports are independent, and cannot be connected to each other at any time.
- All fiber optic ports A, B, and COMMON are duplex, multimode ST ports. Fiber Size: 62.5/125 micron.
- MEMS-Based 1300 nm Mirror Switch supports Gigabyte data rate.
- Transparent to data format and speed.
- Custom length data cables available.



SPECIFICATIONS:

PORT CONNECTORS: (2) ST Duplex female connectors labeled A, and B. (1) RJ45 female 100 Base-TX connector labeled COMMON.

WAVELENGTH: 1300 nm.

FRONT PANEL CONTROLS: (1) Manual pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE: (1) DB9 female connector on rear panel accepts RS232 Serial Data for remote control operation.

POWER: UL approved 110/120 VAC, 60 Hz wall mount power module supplies 12 VDC, 500 mA to the unit. Requires power cable with bayonet locking circular connector provided with the unit.

DIMENSIONS: Desktop 7.5" W x 2.0" H x 7.0" D.
(19.0 x 5.0 x 17.8 cm)

WEIGHT: 3.8 lbs (1.7 kg)

QuickSwitch® Model 6288 ST Duplex A/B Application with RS232 Remote Port

