



SPECIFICATIONS MODEL 7232

Cat. No. 307232

Remote Serial Control

INTRODUCTION

The PathWay® Model 7232 Single Channel RJ45 A/B Switch with RS232 Remote allows the user the capability of sharing a single port interface device connected to the "COMMON" port among two other devices connected to the "A" and "B" ports, with remote access functionality. The Model 7232 is packaged in a slim desktop style enclosure.

The switch may be controlled locally by manually operating the front panel pushbutton or remotely from the DB9 Female Serial Interface Remote port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- Allows quick connection to any one of two devices from one COMMON device.
- All (8) pins of the RJ45 interface are switched via break-beforemake electromechanical relays.
- The switch ports are transparent to data speed and format.
- Unit maintains last set position on power loss and continues to pass data.
- Front panel pushbutton control
- Remote RS232 ACS11 commands that allow the user to control switch position, lockout front panel operations and obtain switch status
- Front panel LEDs display present position and power status.
- Wall mount style case, key-shaping mounting holes on bottom cover.
- Custom length RJ45 cables are available.
- Municipalities, schools, government: This product is on GSA Schedule!



SPECIFICATIONS:

PORT CONNECTORS:

(3) RJ45 connectors labeled A, B, and COMMON

FRONT PANEL CONTROL: (1) Manual Pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE PORT: (1) DB9 female connector on rear panel accepts ASCII RS232 Serial Data for Remote control operation.

POWER: UL approved wall mount 100VAC-240VAC, 50Hz-60Hz power module supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug

DIMENSIONS: 8.15"W x 2.89"H x 7.27"D.

(20.8 x 7.4 x 18.5 cm)

WEIGHT: Approx. 1.7 lbs. (0.8 kg)

WIDE RANGE POWER OPTION AVAILABLE:

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC-240VAC, 50Hz-60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

