

PathWay® Model 7234 Quad-Channel RJ45 Cat5e A/B Switch with Remote Control Port

- **Quickly and easily switch all four RJ45 Cat5e channels simultaneously!**

INTRODUCTION

The PathWay® Model 7234 Quad Channel RJ45 Cat5e A/B Switch with Contact Closure Remote allows the user the capability of accessing two separate devices, ports A and B, via connection through a device connected to the Common port, for each channel. The Model 7234 is enclosed in a 1U, full rack size, all metal, black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

The switch may be controlled manually via the front panel pushbutton or remotely from a DB9 port located on the rear of the unit. Switch position state may be attained via the front panel LED's or from the DB9 Remote port.

FEATURES:

- Each channel allows access to two RJ45 Cat5e networks from one COMMON network or device.
- The switch ports are transparent to all data.
- Eliminates the need to plug and unplug cables.
- All (8) pins of the RJ45 interface are switched via break-before-make electromechanical relays.
- The unit maintains last set position on power loss and continues to pass data.
- Upon power up, the unit switches based on the state of the Contact Closure.
- Front panel pushbutton control.
- Simultaneous control of all channels.
- Remote Contact Closure control and status provides dry contact logic to allow the control of the switch position as well as obtain the present position.
- Front panel LED's display present position and power status.
- Certified for Cat5e compliance.
- Attractive all metal, black box packaging provides EMI/RFI shielding.
- **Custom length RJ45 Cat5e cables available for your switch installation. Get Better performance!**



SPECIFICATIONS:

PORT CONNECTORS: (12) RJ45 female connectors; three labeled A, B, and COMMON for each channel.

FRONT PANEL CONTROL: (1) Manual Pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) DB9 female connector on rear panel accepts dry contact closure switch commands for Remote Control operation.

POWER: UL approved 100VAC-240VAC, 50Hz-60Hz wall mount power module supplies 12VDC, 500mA to the unit. Has 2-prong, US, non-polarized plug.

DIMENSIONS: 19.0"W x 8.0"D x 1.75"H (48.3 x 4.4 x 20.3 cm)

WEIGHT: Approx. 4.9 lbs. (2.2 kg)

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC-240VAC, 50Hz-60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

PathWay® Model 7234 Quad-Channel RJ45 Cat5e A/B Switch Application with Contact Closure Remote

