

LineSelect® Model 7313 3 Channel RJ45 Cat6 A/B Switch, Manual, Simultaneous Control

- Applicable to switching ANY RJ45 interface, quickly and reliably.
- Category 6 Compliant.

INTRODUCTION

The LineSelect® Model 7313 enables each of three RJ45 Cat6 Common ports to select either of two network LANs or devices, via A or B port RJ45 connectors. All three channels of the LineSelect® Model 7313 A/B Switch are switched simultaneously via rotary switch knob located on the front panel.

The unit supports all 8 pins of the RJ45 Cat6 interface. No need to plug and unplug cables thereby eliminating connector wear. The LineSelect® Model 7313 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES:

- Simultaneously switch all three channels of RJ45 A/B via front panel rotary switch knob.
- **Tested for Cat6 compliance.**
- All 8 pins of the RJ45 interface are switched via break-before-make rotary switch.
- High quality sealed switch with self-wiping low impedance contacts.
- Manually operated. No power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Rackmount configuration is standard.
- **Lifetime warranty against manufacturing defects.**

LineSelect® Model 7313



SPECIFICATIONS:

PORT CONNECTORS: (9) RJ45 female connectors, three labeled A, B, and COMMON, for each of the 3 channels.

FRONT PANEL CONTROL: (1) Rotary switch on front panel switches all 3 channels simultaneously.

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 1.75" H x 8.75" D.
(48.3 x 4.4 x 22.3 cm)

WEIGHT: Approximately 4.3 lbs. (2.0 kg)

**Be sure to order
the Cat6 patchcords
at custom lengths
to improve system performance.**

LineSelect® Model 7313 3-Channel RJ45 Cat6 A/B Switch Application

