



SPECIFICATIONS MODEL 7462

Cat. No. 307462

Rath Way Model 7462 8-Channel RJ45 A/B Switch

- Add Reliability to your data network by providing backup switches.
- Switches all 8 pins. Allows compatibility with ALL RJ45 interfaces.
- A Field-Proven High Quality Data Network Switch designed to provide Reliability for Mission Critical Networks!

INTRODUCTION

The PathWay® Model 7462 8-Channel A/B RJ45 Switch allows the user the capability of sharing a device connected to the "COMMON" port among two other devices connected to the "A" and "B" ports for each channel. The Model 7462 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES

- Eight independent RJ45 A/B Switches in a slim 1U high rackmount package.
- All 8 pins of the RJ45 interfaces are switched via break-before-make electromechanical relays.
- The switch ports are transparent to all data.
- Local individual channel control via 8 pushbuttons located on the front panel.
- Front panel LED's indicate each switch position and power status.
- All switched signals are passed via latching copper contact relays that maintain their position and continuity even in the event of a power loss.
- Custom length RJ45 cables available. See Catalog Numbers 990328 thru 990336.

NEED REMOTE CONTROL?

For a similar switch, but with Remote Control added, see Model 7465, Cat. No. 307465.



SPECIFICATIONS:

PORT CONNECTORS: All (24) RJ45(F) ports are located on the rear panel. (8) "A" ports, (8) "B" ports, (8) "Common" ports. **FRONT PANEL CONTROLS:** (8) Manual pushbuttons allow local switching.

DISPLAY: (16) Front panel LED's display switch position and power status.

POWER: UL Approved 100VAC-240VAC, 50Hz-60Hz wall mount power modu\le supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug.


MTBF: 1.8 million hrs (unit alone), 69,800 hrs (unit with power supply included).

DIMENSIONS: 19" W x 1.75" H x 10.3" D.

(48.3 x 4.4 x 26.2 cm) **WEIGHT:** 6.4 lbs. (2.9 kg)

WIDE RANGE POWER OPTION AVAILABLE:

(Cat No 517277) CE, RoHS, and UL listed table mount power module, 100VAC-240VAC, 50Hz-60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. Ideal for international applications.



36 Western Industrial Drive, Cranston, RI 02921 Tel: 401-943-1164 Fax:401-946-5790 www.ElectroStandards.com E-mail:eslab@ElectroStandards.com