(Cat. No. 304161)

# LineSelect Model 8266 DB25 A/B Switch, Manual Operation, Desktop

- A Robust, High Integrity Switch
- No Power Required

#### INTRODUCTION

The *LineSelect*® Model 8266 allows the user to access two DB25 devices connected to the A and B ports from one DB25 device connected to the COMMON port. Switching between devices A and B is quick and easy via the front panel rotary selector - No need to plug and unplug cables. No chance for network reconfiguration errors. The *LineSelect*® Model 8266 is packaged in a compact desktop style enclosure.

#### **FEATURES:**

- Allows access to two networks from one computer or workstation.
- High reliability sealed switch with self-wiping precious metal contacts.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Transparent to data speed and format.
- Manual operation via front panel rotary switch.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Chassis has no feet.
- Custom length DB25 cables available for your switch installation.
- Improves computer network efficiency by allowing sharing of peripherals.
- Lifetime guarantee against manufacturing defects.
- Switches pins 2 through 25 of the DB25 interface. All pins 1(Protective Ground) are tied together and bussed through to eliminate surges.
- Plenum rated insulation on all internal wiring.
- Connector shells are bussed together.
- Rear panel chassis stud accepts spade lug for secure grounding.



### **SPECIFICATIONS:**

## **PORT CONNECTORS:**

(3) DB25 female connectors labeled A, B, and COMMON.

## **FRONT PANEL CONTROLS:**

(1) Rotary Switch allows local switching.

**POWER:** Manually operated. No power required.

**GROUND STUD:** On rear panel.

**DIMENSIONS:** 5.25"W x 2.0"H x 7.25"D.

 $(13.3 \times 5.1 \times 18.4 \text{ cm})$ 

**WEIGHT:** Approximately 1.0 lb. (0.45 kg.)

 Also available with feet. See Model 8265, Cat. No. 509929.

