



**Electro Standards Laboratories**  
ADVANCED SYSTEMS DESIGN & SERVICES



**SPECIFICATIONS**  
**MODEL 8652**  
Cat. No. 304110

## **LineSelect® Model 8652 DB25 RS232 A/B/C/D/E/F Switch, Desktop, Manual Operation**

- **Applicable to switching ANY RJ45 Interface Device.**
- **Field Proven, Highly Reliable!**
- **Switch between devices without having to disconnect cables.**

### **INTRODUCTION**

The LineSelect® Model 8652 DB25 RS232 A/B/C/D/E/F Switch allows the user the capability of sharing a DB25 interface device connected to the "COMMON" port among six other devices connected to the "A", "B", "C", "D", "E", and "F" ports. The LineSelect® Model 8652 is enclosed in a 2U, all metal black chassis designed to provide EMI/RFI shielding and be used as a desktop unit.

### **FEATURES:**

- Allows quick connection to any one of six devices from one COMMON device.
- High quality sealed switch with self-wiping low impedance contacts.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Transparent to data speed and format.
- Manual operation via front-panel rotary switch.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB25 cables available for your switch installation.
- All 25 pins of the DB25 interface are switched.
- Improves computer network efficiency by allowing sharing of peripherals.
- **Lifetime guarantee against manufacturing defects.**

### **LineSelect® Model 8652**



### **SPECIFICATIONS:**

**PORT CONNECTORS:** (7) DB25 female connectors labeled A, B, C, D, E, F and COM.

**FRONT PANEL CONTROL:** (1) Rotary switch on front panel selects A, B, C, D, E, or F.

**POWER:** No power required. Manually operated.

**DESKTOP ENCLOSURE:** 8.1"W x 3.47"H x 7.74"D. (20.6 x 8.9 x 19.7 cm)

**WEIGHT:** 2 lbs. (0.9 kg)

**Ask about our popular**  
Model 700  
RS232 Breakout Box  
Tri-State LED's  
monitor the data interface  
and "TELL ALL"  
for fault isolation.



### **LineSelect® Model 8652 Application**

