



SPECIFICATIONS MODEL 9085R

(Cat. No. 309085R)

LineSelect Model 9085R RJ45 A/B Switch, Remotely Controllable, DIN Rail Mounted,

Cat5e, RoHS and REACH Compliant

- Convenient DIN rail mounting!
- Ideal for use in process control systems requiring switching between multiple Programmable Logic Controllers (PLC's)
 INTRODUCTION

The LineSelect® Model 9085R RJ45 A/B switch allows the user to access two RJ45 devices connected to it's A and B ports with one RJ45 device connected to its COMMON port. The unit is controlled by the presence or absence of a 24VDC signal applied to its Control Port. The LineSelect® Model 9085R switch is easily integrated as a system component by utilizing its rear panel DIN rail mounting bracket.

OPERATION

When 24VDC is not applied to the Control Port, the unit will be in the "A" position and the POSITION LED will be OFF. When 24VDC is applied to the Control Port, the unit will be in its "B" position and the POSITION LED will be ON.

FEATURES:

- Allows (1) COMMON RJ45 port to be shared among either of (2) RJ45 ports "A" and "B".
- Controlled by 24VDC signal applied to Control Port.
- Switches all 8 leads of the RJ45 interface via break-before-make electromechanical relays.
- Certified for category 5e compliance.
- RoHS, and REACH, compliant.
- DIN rail bracket on rear panel.

Specifications:

PORT CONNECTORS: (3) RJ45 female connectors labeled A, B, and COMMON.

CONTROL PORT: (1) Barrier strip accepts 24VDC, 50mA control signal to switch unit between its "A" and "B" position.


DISPLAY: (1) Front panel LED displays switch position. DIMENSIONS: DIN Rail Mount Package: 1.75"W x 4.25"H x 6.0"D. (4.4 x 10.8 x 15.2 cm)

WEIGHT: Approximately 1.1 lbs. (0.5 kg)





Cat5e patchcords - ideal for 10BASE-T, 100BASE-T, 1000BASE-T Ethernet and Gigabyte Ethernet				
Color	3 ft.	5 ft.	10 ft.	25 ft.
Black	990328-003	990328-005	990328-010	990328-025
Red	990333-003	990333-005	990333-010	990333-025
Yellow	990336-003	990336-005	990336-010	990336-025



36 Western Industrial Drive, Cranston, RI 02921 Tel: 401-943-1164 Fax:401-946-5790 www.ElectroStandards.com E-mail: eslab@ElectroStandards.com