

LineSelect® Model 9435 DB9-Male A/B/C/D Switch, Manual, Rackmount

- **Ideal for device-sharing applications; Applicable to ANY DB9 interface devices.**

INTRODUCTION

The **LineSelect®** Model 9435 DB9 A/B/C/D Switch allows the user to reroute data between any one of four devices to one COMMON device with the simple rotation of a selector switch. All nine pins of the DB9 interface are supported. No need to plug and unplug interconnection cables thereby eliminating connector wear and/or errors when reconfiguring networks. The **LineSelect®** Model 9435 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES

- Allows quick connection to any one of four devices from one COMMON port.
- Manual operation via front-panel rotary switch.
- High quality sealed switch with self-wiping precious metal contacts.
- Eliminates the need to plug and unplug cables.
- Transparent to data speed and format.
- All 9 pins of the DB9 interface are switched via break-before-make rotary switch.
- No external power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length DB9 cables available for your switch installation.
- Lifetime warranty against manufacturing defects.
- **Capable of handling 28VDC, 0.5ADC.**
- **Uses 22 AWG wire.**



SPECIFICATIONS:

PORT CONNECTORS: (5) DB9 male connectors on rear panel labeled A, B, C, D, and COMMON.

FRONT PANEL CONTROL: (1) Rotary switch on front panel selects A, B, C, or D.

POWER: No power required. Manually operated.

DIMENSIONS: 19.0" W x 1.75" H x 8.8" D.
(48.3 x 4.4 x 22.4 cm)

WEIGHT: Approximately 4.1 lbs. (1.9 kg)

Custom Length DB9 cables available for your switch installation. State cable length (XXX) when ordering.

Part Number	Description
990127-XXX	XXX Feet, DB9 F/F, 9-Conductor Unshielded PVC Cable
990125-XXX	XXX Feet, DB9 M/F, 9-Conductor Unshielded PVC Cable
990126-XXX	XXX Feet, DB9 M/M, 9-Conductor Unshielded PVC Cable

