

LineSelect® Model 9461 RJ45 3-Channel Switch, 2-Channels RJ45 ONLINE/OFFLINE, 1-Dual Channel A/B

- Quick and Easy **ONLINE/OFFLINE** Connection!
- Certified for **Cat5e** Compliance.

INTRODUCTION

The **LineSelect®** Model 9461 Three Channel Switch allows simultaneous switching of Channel 1 (Dual Channel A/B Switch) and **ONLINE/OFFLINE** switching for Channel 2 and Channel 3. No need to plug and unplug cables thereby eliminating connector wear. The **LineSelect®** Model 9461 is enclosed in a slim 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES:

- Manually control each of three channels independently via the (3) Rotary manual switches located on the front panel:
 - o (2) Rotary manual switches; 1 for each **ONLINE/OFFLINE** switch.
 - o (1) Rotary manual switch for the dual channel **A/B** switch.
- **Tested for Cat5e compliance.**
- All (10) RJ45 Female ports are located on the rear panel.
- Transparent to data speed and format.
- All (8) pins of the RJ45 interface are switched.
- High quality sealed break-before-make switches with self-wiping low impedance contacts.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length Cat5e cables for your switch installation.
- Lifetime warranty against manufacturing defects.



SPECIFICATIONS:

CH1 PORT CONNECTORS: (6) RJ45 female connectors: (3) labeled A1, B1, and COM 1 and (3) labeled A2, B2, and COM 2.

CH2 PORT CONNECTORS: (2) RJ45 female connectors labeled A and B.

CH3 PORT CONNECTORS: (2) RJ45 female connectors labeled A and B.

CH1 FRONT PANEL CONTROL: (1) Rotary switch selects A or B.

CH2 and CH3 FRONT PANEL CONTROL: Each has (1) Rotary switch to select **ONLINE** or **OFFLINE**.

POWER: No power required. Manually operated

DIMENSIONS: 19" w X 1.75" h X 8.0" D
(48.3 x 4.4 x 20.4 cm)

WEIGHT: 4.2 lbs. (1.9 kg)

