

LineSelect® Model 9503 Tri-Channel Switch, DB25 A/B/C/D/E/F, DB25 A/B, and BNC A/B, Manual, Rackmount

INTRODUCTION:

The LineSelect® Model 9503 Switch system is comprised of three independent sharing switches efficiently packaged in a 19-inch wide 2U high (3.5") rackmount unit. The switch functions are described and illustrated below.

FEATURES:

- Independently switch each of the three channels manually via three knobs located on the front panel, one knob per channel.
- **Channel 1:** DB25 A/B/C/D/E/F Switch with (7) DB25 female connectors for ports "A", "B", "C", "D", "E", "F" and "Common", all 25 leads switched.
- **Channel 2:** DB25 A/B Switch with (3) DB25 female connectors for ports "A", "B" and "Common", all 25 leads switched.
- **Channel 3:** BNC A/B Switch with (3) BNC female connectors for ports "A", "B" and "Common", center conductor and shield switched.
- All ports located on rear panel.
- Rackmount style chassis, 19" Wide x 3.5" High x 8" Deep.
- Manual operation. No power required.
- High reliability, precious metal, sealed switches.
- Custom length DB25 cables and BNC cables are available for your switch installation.



SPECIFICATIONS:

CHANNEL -1 PORT CONNECTORS: (7) DB25 female connectors, custom labeled A, B, C, D, E, F and COMMON.

CHANNEL -2 PORT CONNECTORS: (3) DB25 female connectors, custom labeled A, B, and COMMON.

CHANNEL -3 PORT CONNECTORS: (3) BNC female connectors, labeled A, B, and COMMON.

FRONT PANEL CONTROLS: (3) Rotary switch on front panel allow for local switching

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 3.5" H x 8.0" D. (48.3 x 8.9 x 20.4 cm)

WEIGHT: Approximately 5.0 lbs. (2.27 kg)

Model 9503 Tri-Channel DB25/BNC Switch Function Diagram

