

Bantam Plug and WE310 Plug Interface Telephone / Telecom Field Technician Test Kit

- Kit contains thirteen high quality cables designed to facilitate test and access of high speed data interfaces.
- Designed with input from telco telecom installers, telco linesmen and field technicians.
- Compatible with all standard phone system and telephone test equipment.

Electro Standards Laboratories manufactures a complete selection of telephone/telecom patch cables that are compatible with all standard telephone systems, data and voice test equipment, and patch/interconnect devices. All of the cables are of the highest quality, manufactured in U.S.A. Custom designed cables utilizing these standard connectors are also available.

- An excellent companion to your present Telecom Tool Kit.
- Test Kit contains thirteen cables designed to facilitate test and access of high speed data interfaces.
- All cables are packaged in a handy Test Kit Carry Case for maximum protection.
- Includes an information manual delineating each cable configuration.

• **IMPORTANT!!! Custom-design cables and Custom-content kits available to suit your specific needs. Specify the test cable you would like in a kit and request a quote.**

Model 930849 Telephone Test Kit W/ Bantam Plug & WE310 Cables



13
Test Cables

The #930849 TEST KIT contains:

Qty.	Catalog No.	Length	Description
2	930840-006	6 Ft.	Cables: Bantam Plug/Bantam Plug
2	930841-006	6 Ft.	Cables: Bantam Plug/Two Telco Piercing Alligator Clips
3	930842-006	6 Ft.	Cables: WE310 Plug/Bantam Plug
3	930843-005	5 Ft.	Cables: WE310 Plug/Two Telco Piercing Alligator Clips
1	930844-006	6 Ft.	Cable: DB-15 Female/Two Bantam Plugs, T-1
1	930845-006	6 Ft.	Cable: DB-15 Male/Two Bantam Plugs, T-1
1	930847-006	6 Ft.	Cable: RJ-48 Plug/Two Bantam Plugs
1	930848	-- --	Test Kit Carry Case

BANTAM PLUG/BANTAM PLUG


Two miniature 3-conductor **nickel phone plugs**, connected by shielded paired cable having a **high-flex PVC** jacket. The standard length is 6 feet. Custom lengths available on request.



Cat#930840-006 Length 6 Ft.

BANTAM PLUG/TWO TELCO PIERCING ALLIGATOR CLIPS

A miniature 3-conductor **nickel phone plug** connected to two piercing alligator clips having one red and one black vinyl boot. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket.



Cat#930841-006 Length 6 Ft.

more →

WE310 PLUG/BANTAM PLUG

A PJ-051 nickel phone plug and a miniature 3-conductor **nickel phone plug** connected by shielded paired cable having a **high-flex PVC** jacket. Standard lengths are 3 feet, 5 feet, and 6 feet.



Cat#930842-006 Length 6 Ft.

WE310 PLUG/TWO TELCO PIERCING ALLIGATOR CLIPS

A PJ-051 **nickel phone plug** connected to two piercing alligator clips having one red and one black vinyl boot. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Standard lengths are 5 feet and 10 feet.



Cat#930843-005 Length 5 Ft.

DB-15 FEMALE/TWO BANTAM PLUGS, T-1


A DB-15 female connector, metal hood with thumbscrews, connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Paired: Pins 1 & 9 to TX Tip & Ring, pins 3 & 11 to RX Tip & Ring. Standard length is 6 feet. The TX plug is RED, the RX plug is BLACK.



Cat#930844-006 Length 6 Ft.

DB-15 MALE/TWO BANTAM PLUGS, T-1


A DB-15 male connector, metal hood with thumbscrews, connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Paired: Pins 1 & 9 to TX Tip & Ring, pins 3 & 11 to RX Tip & Ring. The TX phone plug is Red, the RX phone plug is BLACK.



Cat#930845-006 Length 6 Ft.

RJ-48 PLUG/TWO BANTAM PLUGS

An RJ-48 plug with molded grip connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded twisted pair with **high-flex PVC** jacket. Paired: Pins 5 & 4 to TX Tip & Ring, pins 2 & 1 to RX Tip & Ring. Standard length is 6 feet. The TX plug is RED, the RX plug is black.



Cat#930847-006 Length 6 Ft.

TEST KIT CARRY CASE

A convenient carry case for the test leads. Size: 8 x 11 x 3 inches. Provides protection for the cables and connectors. Zippered. A separator and an outside pocket provides compartments for manuals.




Cat#930848 Carry Case

OPTIONALLY AVAILABLE CABLE

BANTAM PLUG/TWO MINI-GRAB TEST HOOKS

A miniature 3-conductor **nickel phone plug** connected to two mini-grab test hooks having one red and one black body. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket.



Cat#940322-006 Length 6 Ft.

